

Page 1/10

Fax: 0049-(0)7223-284-245

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 16.10.2017 Version number 9 Revision: 13.08.2017

# SECTION 1: Identification of the substance/mixture and of the company/undertaking

- · 1.1 Product identifier
- · Trade name: UHU greenit +150°C
- 1.2 Relevant identified uses of the substance or mixture and uses advised against No further relevant information available.
- · Application of the substance / the mixture Adhesives
- · 1.3 Details of the supplier of the safety data sheet
- Manufacturer/Supplier:

UHU GmbH & Co.KG

Herrmannstraße 7

D-77815 Bühl (Baden)

Tel.:0049-(0)7223-284-0

email: info@uhu.boltongroup.de

- · Further information obtainable from: UHU QESH
- · 1.4 Emergency telephone number:

Tel.: + 49 (0) 30/19240 (Notruf)

Tel.: + 49 (0) 72 23/28 40

#### **SECTION 2: Hazards identification**

- · 2.1 Classification of the substance or mixture
- Classification according to Regulation (EC) No 1272/2008



GHS02 flame

Flam. Liq. 2 H225 Highly flammable liquid and vapour.



GHS07

Eye Irrit. 2 H319 Causes serious eye irritation.

Aquatic Chronic 3 H412 Harmful to aquatic life with long lasting effects.

- · 2.2 Label elements
- Labelling according to Regulation (EC) No 1272/2008

The product is classified and labelled according to the CLP regulation.

· Hazard pictograms





GHS02 GHS07

- · Signal word Danger
- · Hazard statements

H225 Highly flammable liquid and vapour.

(Contd. on page 2)





# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 16.10.2017 Version number 9 Revision: 13.08.2017

Trade name: UHU greenit +150°C

(Contd. of page 1)

H319 Causes serious eye irritation.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements

P101 If medical advice is needed, have product container or label at hand.

P102 Keep out of reach of children.

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition

sources. No smoking.

P303+P361+P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin

with water/shower.

P501 Dispose of contents/container in accordance with local/regional/national/

international regulations.

· Additional information:

Contains Rosin. May produce an allergic reaction.

· 2.3 Other hazards

· Results of PBT and vPvB assessment

PBT: Not applicable.vPvB: Not applicable.

### **SECTION 3: Composition/information on ingredients**

· 3.2 Mixtures

· **Description:** Adhesive

· Dangerous components:		
CAS: 67-64-1 EINECS: 200-662-2 Reg.nr.: 01-2119471330-49-XXXX	acetone      Flam. Liq. 2, H225;    Eye Irrit. 2, H319; STOT SE 3, H336	10-25%
CAS: 141-78-6 EINECS: 205-500-4 Reg.nr.: 01-2119475103-46-XXXX	ethyl acetate  String Flam. Liq. 2, H225; Strit. 2, H319; STOT SE 3, H336	10-25%
CAS: 110-54-3 EINECS: 203-777-6	n-hexane ♦ Flam. Liq. 2, H225; ♦ Repr. 2, H361f; STOT RE 2 H373; Asp. Tox. 1, H304; ♦ Aquatic Chronic 2, H411; ♦ Skin Irrit. 2, H315; STOT SE 3, H336	1-2.5%
CAS: 8050-09-7 EINECS: 232-475-7 Reg.nr.: 01-2119480418-32-xxxx	Rosin Skin Sens. 1, H317	<1%
CAS: 1314-13-2 EINECS: 215-222-5	zinc oxide  Aquatic Acute 1, H400; Aquatic Chronic 1, H410	<1%

• Additional information: For the wording of the listed hazard phrases refer to section 16.

## **SECTION 4**: First aid measures

· 4.1 Description of first aid measures

· General information: No special measures required.

(Contd. on page 3)



Page 3/10

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 16.10.2017 Version number 9 Revision: 13.08.2017

Trade name: UHU greenit +150°C

(Contd. of page 2)

- · After inhalation: Supply fresh air; consult doctor in case of complaints.
- After skin contact: Generally the product does not irritate the skin.
- · After eye contact:

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

- After swallowing: Do not induce vomiting; call for medical help immediately.
- 4.2 Most important symptoms and effects, both acute and delayed

No further relevant information available.

4.3 Indication of any immediate medical attention and special treatment needed

No further relevant information available.

# **SECTION 5: Firefighting measures**

- 5.1 Extinguishing media
- · Suitable extinguishing agents:

CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

- For safety reasons unsuitable extinguishing agents: Water with full jet
- 5.2 Special hazards arising from the substance or mixture

No further relevant information available.

- 5.3 Advice for firefighters
- · Protective equipment: No special measures required.

### **SECTION 6: Accidental release measures**

- 6.1 Personal precautions, protective equipment and emergency procedures Ensure adequate ventilation
- **6.2 Environmental precautions:** Do not allow to enter sewers/ surface or ground water.
- 6.3 Methods and material for containment and cleaning up:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Send for recovery or disposal in suitable receptacles.

Ensure adequate ventilation.

6.4 Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

### **SECTION 7: Handling and storage**

- · 7.1 Precautions for safe handling No special precautions are necessary if used correctly.
- Information about fire and explosion protection:

Keep ignition sources away - Do not smoke.

Protect against electrostatic charges.

- · 7.2 Conditions for safe storage, including any incompatibilities
- · Storage:
- · Requirements to be met by storerooms and receptacles: Store in a cool location.

(Contd. on page 4)





# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 16.10.2017 Version number 9 Revision: 13.08.2017

Trade name: UHU greenit +150°C

(Contd. of page 3)

- $\cdot \mbox{ Information about storage in one common storage facility: } \mbox{Not required}.$
- Further information about storage conditions:

Keep container tightly sealed.
Store in cool, dry conditions in well sealed receptacles.

- Storage class: 3
- · 7.3 Specific end use(s) No further relevant information available.

3.1 Contro		nation about design of technical faciliti	
	•	limit values that require monitoring at	the workplace:
67-64-1 ac		mine values that require memoring at	the Wernplace.
OELV (EL	J)	Long-term value: 1210 mg/m³, 500 ppm	
AGW (Germany) Long-term value: 1200 mg/m³, 500 ppm 2(I);AGS, DFG, EU, Y			
41-78-6 €	thyl ac	cetate	
OELV (EU	,	Short-term value: 1468 mg/m³, 400 ppm Long-term value: 734 mg/m³, 200 ppm	
,	,	Long-term value: 1500 mg/m³, 400 ppm 2(I);DFG, Y	
l10-54-3 r		1 <del>e</del>	
OELV (EL	J)	Long-term value: 72 mg/m³, 20 ppm	
AGW (Ger	many)	Long-term value: 180 mg/m³, 50 ppm 8(II);DFG, EU, Y	
3050-09-7	Rosin		
ИАК (Gerr	many)	vgl.Abschn.IV	
ONELs			
67-64-1 ac	etone		
Oral	Consu	mer DNEL, longterm oral	62 mg/kg bw/day
Dermal	Consu	mer DNEL, longterm dermal	62 mg/kg bw/day
nhalative	Consu	mer DNEL, longterm inhalation	200 mg/m³
41-78-6 €	thyl ac	cetate	
Oral	Consumer DNEL, chronic effect oral		4.5 mg/kg (_)
Dermal	al Consumer DNEL, chronic effect dermal		37 mg/kg (_)
nhalative	Consumer DNEL, acute inhalation		734 mg/m³ (_)
	Verbra	ucher, Chronische Wirkungen, Einatmen	367 kg/m³ (_)
PNECs			
67-64-1 ac	etone		
PNEC Fre	sh wate	er   10.6 mg/l	

EU-EN



Page 5/10



# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 16.10.2017 Version number 9 Revision: 13.08.2017

Trade name: UHU greenit +150°C

		_
	(Contd. of page 4)	j
PNEC Marine wat	er 1.06 mg/l	
PNEC Soil	29.5 mg/kg	
141-78-6 ethyl acetate		
PNEC Fresh wate	r   0.24 mg/l (_)	
PNEC Marine wat	er 0.024 mg/l (_)	
PNEC Soil	0.148 mg/kg (_)	
· Ingredients with	biological limit values:	
67-64-1 acetone		
	80 mg/l Untersuchungsmaterial: Urin Probennahmezeitpunkt: Expositionsende bzw. Schichtende Parameter: Aceton	
110-54-3 n-hexan	е	
	5 mg/l Untersuchungsmaterial: Urin Probennahmezeitpunkt: Expositionsende bzw. Schichtende Parameter: 2.5-Hexandion plus 4.5-Dihydroxy-2-hexanon (nach Hydrolyse)	

- · Additional information: The lists valid during the making were used as basis.
- · 8.2 Exposure controls
- Personal protective equipment:
- General protective and hygienic measures:

The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

Avoid direct contact with the chemical/ the product/ the preparation by organisational measures.

- · Respiratory protection: Not necessary if room is well-ventilated.
- · Protection of hands:

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

#### Material of gloves

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

#### Penetration time of glove material

The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.

Eye protection: Goggles recommended during refilling

EU-EN





# Safety data sheet according to 1907/2006/EC, Article 31

Revision: 13.08.2017 Printing date 16.10.2017 Version number 9

Trade name: UHU greenit +150°C

(Contd. of page 5)

9.1 Information on basic physical and of General Information	chemical properties
Appearance: Form:	Fluid
Colour:	Light yellow
Odour:	Characteristic
Odour threshold:	Not determined.
pH-value:	Not determined.
Change in condition Melting point/freezing point: Initial boiling point and boiling range	Undetermined. : 55 °C
Flash point:	-17 °C
Flammability (solid, gas):	Not applicable.
Ignition temperature:	460 °C
Decomposition temperature:	Not determined.
Auto-ignition temperature:	Product is not selfigniting.
Explosive properties:	Product is not explosive. However, formation of explosive air/vapour mixtures are possible.
Explosion limits:	
Lower:	2.1 Vol %
Upper:	13 Vol %
Vapour pressure at 20 °C:	233 hPa
Density:	Not determined.
Relative density	Not determined. Not determined.
Vapour density Evaporation rate	Not determined.
Solubility in / Miscibility with	
water:	Not miscible or difficult to mix.
Partition coefficient: n-octanol/water:	Not determined.
Viscosity:	
Dynamic:	Not determined.
Kinematic:	Not determined.
Solvent content:	
Organic solvents:	32.2 %
Water:	0.2 %
VOC (EC)	32.17 %

(Contd. on page 7)

EU-EN



Page 7/10

# Safety data sheet according to 1907/2006/EC, Article 31

Printing date 16.10.2017 Version number 9 Revision: 13.08.2017

Trade name: UHU greenit +150°C

(Contd. of page 6)

Solids content: 67.7 %

• 9.2 Other information All relevant physical data were determined for the

mixture. All non determined data are not measurably or not relevant for the characterization of the mixture.

### **SECTION 10: Stability and reactivity**

- · 10.1 Reactivity No further relevant information available.
- · 10.2 Chemical stability
- Thermal decomposition / conditions to be avoided:

No decomposition if used according to specifications.

- · 10.3 Possibility of hazardous reactions No dangerous reactions known.
- 10.4 Conditions to avoid No further relevant information available.
- · 10.5 Incompatible materials: No further relevant information available.
- 10.6 Hazardous decomposition products: No dangerous decomposition products known.

### **SECTION 11: Toxicological information**

- · 11.1 Information on toxicological effects
- · Acute toxicity Based on available data, the classification criteria are not met.

· LD/LC50 \	/alues rele	evant for classification:
67-64-1 ad	cetone	
Oral	LD50	5,800 mg/kg (rat)
141-78-6 €	141-78-6 ethyl acetate	
Oral	LD50	5,620 mg/kg (rabbit)
Inhalative	LC50/4 h	1,600 mg/l (rat)
1314-13-2	zinc oxid	e
Oral	LD50	>5,000 mg/kg (rat)

- · Primary irritant effect:
- · Skin corrosion/irritation Based on available data, the classification criteria are not met.
- Serious eye damage/irritation Causes serious eye irritation.
- Respiratory or skin sensitisation Based on available data, the classification criteria are not met.
- · Germ cell mutagenicity Based on available data, the classification criteria are not met.
- · Carcinogenicity Based on available data, the classification criteria are not met.
- · Reproductive toxicity Based on available data, the classification criteria are not met.
- STOT-single exposure Based on available data, the classification criteria are not met.
- · STOT-repeated exposure Based on available data, the classification criteria are not met.
- · Aspiration hazard Based on available data, the classification criteria are not met.

EU-EN



Page 8/10

### Safety data sheet according to 1907/2006/EC, Article 31

Printing date 16.10.2017 Version number 9 Revision: 13.08.2017

Trade name: UHU greenit +150°C

(Contd. of page 7)

### **SECTION 12: Ecological information**

- · 12.1 Toxicity
- Aquatic toxicity: No further relevant information available.
- 12.2 Persistence and degradability No further relevant information available.
- · 12.3 Bioaccumulative potential No further relevant information available.
- · 12.4 Mobility in soil No further relevant information available.
- · Ecotoxical effects:
- · Remark: Harmful to fish
- · Additional ecological information:
- **General notes:**

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water Harmful to aquatic organisms

Do not allow product to reach ground water, water course or sewage system.

- · 12.5 Results of PBT and vPvB assessment
- · PBT: Not applicable.
- · vPvB: Not applicable.
- 12.6 Other adverse effects No further relevant information available.

### **SECTION 13: Disposal considerations**

- · 13.1 Waste treatment methods
- Recommendation

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Disposal must be made according to official regulations.

### · European waste catalogue

08 04 09\* waste adhesives and sealants containing organic solvents or other hazardous substances

- Uncleaned packaging:
- · Recommendation: Disposal must be made according to official regulations.

14.1 UN-Number	
ADR, IMDG, IATA	UN1133
14.2 UN proper shipping name	
ADR	1133 ADHESIVES, special provision 640D 1133 KLEBSTOFFE, UMWELTGEFÄHRDEN Sondervorschrift 640D
IMDG, IATA	ADHESIVES





## Safety data sheet according to 1907/2006/EC, Article 31

Revision: 13.08.2017 Printing date 16.10.2017 Version number 9

Trade name: UHU greenit +150°C

(Contd. of page 8)

· 14.3 Transport hazard class(es)

· ADR, IMDG, IATA



· Class 3 Flammable liquids. · Label

· ADR, IMDG, IATA

· 14.4 Packing group

· 14.5 Environmental hazards: · Marine pollutant: Yes

· 14.6 Special precautions for user Warning: Flammable liquids.

Danger code (Kemler): 33 · EMS Number: F-E,S-D · Stowage Category В

· 14.7 Transport in bulk according to Annex II

of Marpol and the IBC Code Not applicable.

· Transport/Additional information:

· Limited quantities (LQ)

Code: E2 · Excepted quantities (EQ)

Maximum net quantity per inner packaging: 30 ml

Maximum net quantity per outer packaging: 500 ml

Transport category · Tunnel restriction code D/E

· Limited quantities (LQ) 5L

· Excepted quantities (EQ)

Maximum net quantity per inner packaging: 30 ml Maximum net quantity per outer packaging: 500 ml

UN 1133 ADHESIVES, SPECIAL PROVISION UN "Model Regulation":

640D, 3, II

### **SECTION 15: Regulatory information**

- 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture
- · Directive 2012/18/EU
- · Named dangerous substances ANNEX I None of the ingredients is listed.

(Contd. on page 10)





## Safety data sheet according to 1907/2006/EC, Article 31

Printing date 16.10.2017 Version number 9 Revision: 13.08.2017

Trade name: UHU greenit +150°C

(Contd. of page 9)

- Seveso category P5c FLAMMABLE LIQUIDS
- · Qualifying quantity (tonnes) for the application of lower-tier requirements 5,000 t
- · Qualifying quantity (tonnes) for the application of upper-tier requirements 50,000 t
- · REGULATION (EC) No 1907/2006 ANNEX XVII Conditions of restriction: 3
- 15.2 Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

#### **SECTION 16: Other information**

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

#### Relevant phrases

- H225 Highly flammable liquid and vapour.
- H304 May be fatal if swallowed and enters airways.
- H315 Causes skin irritation.
- H317 May cause an allergic skin reaction.
- H319 Causes serious eye irritation.
- H336 May cause drowsiness or dizziness.
- H361f Suspected of damaging fertility.
- H373 May cause damage to organs through prolonged or repeated exposure.
- H400 Very toxic to aquatic life.
- H410 Very toxic to aquatic life with long lasting effects.
- H411 Toxic to aquatic life with long lasting effects.

#### · Department issuing SDS: UHU QESH

· Contact: Dr. C. Hanf

### Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the

International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

GHS: Globally Harmonised System of Classification and Labelling of Chemicals

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

VOC: Volatile Organic Compounds (USA, EU)

DNEL: Derived No-Effect Level (REACH)

PNEC: Predicted No-Effect Concentration (REACH)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative

Flam. Liq. 2: Flammable liquids – Category 2 Skin Irrit. 2: Skin corrosion/irritation – Category 2

Eye Irrit. 2: Serious eye damage/eye irritation - Category 2

Skin Sens. 1: Skin sensitisation - Category 1

Repr. 2: Reproductive toxicity - Category 2

STOT SE 3: Specific target organ toxicity (single exposure) – Category 3 STOT RE 2: Specific target organ toxicity (repeated exposure) – Category 2

Asp. Tox. 1: Aspiration hazard - Category 1

Aquatic Acute 1: Hazardous to the aquatic environment - acute aquatic hazard - Category 1

Aquatic Chronic 1: Hazardous to the aquatic environment - long-term aquatic hazard - Category 1

Aquatic Chronic 2: Hazardous to the aquatic environment - long-term aquatic hazard – Category 2 Aquatic Chronic 3: Hazardous to the aquatic environment - long-term aquatic hazard – Category 3

\* Data compared to the previous version altered.